









-  Blends oxygen and air
-  Built in blower reaches a flow rate of up to 60 liters per minute
-  Humidifier
-  Pre-heating of oxygen/air blend to 37°C
-  Simple to operate
-  Designed for continuous operation

SPECIFICATION

Order codes	- HF60L-E-110VAC - HF60L-E-230VAC
Power	40 W-90 W
Flow	2-60 l/min
Heater	5 level heating control
Humidifier	5 level humidity control
Oxygen and Flow Sensor	N/A
Liquid tank	650 ml
Weight	4,5 kg
Heater	Max. 38°C
Operating temperature range	18°C ~ 35°C
Operation type	Continuous

ACCESSORIES COMING WITH THE PRODUCT:

Reusable:

- Liquid tank
- Oxygen input adapter
- Heater cable
- Power cable (Schuko plug)

Consumable:

- Medical bacterial filter
- Hose kit

Accessories (consumables)



NC01L, NC01M, NC01S
Patient Interface
(Nasal Cannula)
Large, Medium, Small




HFAAF
Bacterial Filter



HFHS1
Hose set
Breathing & Short tubes



PSCBS
Pole with water feeding bottle
and accessories

 **ELMASLAR**
İmalat Tibbi Cihazlar İthalat İhracat A.Ş.
ASO 1. Org. San. Bölgesi Babürşah Cad. No: 17
Sincan/ANKARA/TURKIYE